

Edge Sport

SAE 10W-60 Race proven for highly stressed and competition engines

Applications

Castrol EDGE Sport 10W-60 is a hard wearing product for use in a wide range of sports performance engines. This product has been tested in race engines to deliver protection in hot and hard running scenarios.

Castrol EDGE Sport 10W-60 is suitable for tuned or high performance vehicles.

Features / Benefits

Delivers race proven power and performance for highly tuned, competition engines.

Provides strength in reserve.

Protects even when fast, hot or hard running.

Synthetic technology.

Specifications / Performance

ACEA A3/B3/B4 API SL/CF

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Edge Sport

SAE 10W-60 Race proven for highly stressed and competition engines

Health, Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures, together with environmental effects and disposal of used products.

Castrol (UK) Ltd. or its subsidiaries will not accept liability if the product is used other than in the manner or with the precautions or for the purpose/s specified. Before the product is used other than as directed, advice should be obtained from the local Castrol office.

Typical	Typical Characteristics						
		Test Methods	Units	Value:			
SAE	10W-60						

Test	Method(s)	Unit	Typical
Relative Density 15°C	ASTM D4052		0.838
Appearance	Visual		bright and clear
Viscosity 100°C	ASTM D445	mm²/s	23.5
Viscosity 40°C	ASTM D445	mm²/s	174
Viscosity Index	ASTM D2270	None	164
CCS -25C	ASTM D5293	cР	6100
Ash, Sulphated	ASTM D874	% wt	1.2
Total Base Number, TBN	ASTM D2896	mg KOH/g	10.2

The above figures are typical of those obtained with normal production tolerance and do not constitute a specification.

This Data sheet and information it contains is considered to be accurate at the date of printing. No warranty or representation, expressed or implied, is made as to the accuracy or completeness of the data and information contained in this publication.

It is the User's obligation to evaluate and use products safely and within the scope advised in the data sheet and to comply with all applicable laws and regulations. No statement made in this publication shall be construed as a permission, recommendation or authorisation given or implied to practice any patented invention without a valid licence.

The Seller shall not be responsible for any loss or damage resulting from any hazards or risks identified in the data sheet and which are associated with petroleum products concerned (provided that this disclaimer shall not affect any statutory rights of the Buyer of the petroleum products concerned).

Castrol (UK) Ltd Wakefield House Pipers Way Swindon Wiltshire SN3 1RE

Lubricants Helpline: Orders/Enquiries: 01793 452222 08459 123011